

Much more than just your average safe!



Composite Insulation
Provides heat protection for the locks & bolts.

Concealed Door Hinges Internal hinges are shielded against attacks.

All-over Gripping Rail
Runs across the hinge side.



Rotating 25mm Round Bolts Additional protection against drilling & attack.



3 Security Standards

- Level B according to VDMA24992, 5/95
- Level S 2 according to DIN EN 14450
- fire resistance LFS 30 P according to EN 15659 30 min fire protection for paper

COMBILINE

Dimensions

CL-20 320 x 435 x 380mm CL-20 360 x 495 x 445mm CL-40 560 x 495 x 445mm







CI 4

Purchase 3 or more Combi-Line Safes & receive a FREE Steel Shop Display Stand









Fire rating
30 min fire protection

Security rating protection against burglary

Up to \$33,000 Insurance rating**











Sales Incentive Claim Form

Receive pre-loaded gift cards for Every Safe Sold*

CL-10 • \$20

CL-20 • \$30

CL-40 • \$40

*Valid till 30 September 2019.

Business Name		Staff Member			
Date From		Date To			
	_				
Combi-Line Safe/s Sold					
Fingerscan QTY	Electronic	QTY	Keyed		QTY
CL-10E FS	C	L-10E		CL-10S	
CL-20E FS		L-20E		CL-20S	
CL-40E FS	C	L-40E		CL-40S	
Total Sales	Business Owner	(Sign to Confirm)		
NOTES.					

- **1.** Please attach proof of sale for each safe behind this form.
- 1 form per staff member.
- E-mail or fax this completed form back to SIEPER Group H/O

Fax: Australia - 02 9748 0566 New Zealand - 09 281 2301

Email: sales@siepergroup.com

Office Use Only

Date Received Allocated Dispatched Status